

## RIDEMAX FL 693 M - Especificaciones técnicas



### Description

RIDEMAX FL 693 M es el neumático ideal para quien tiene que desplazarse frecuentemente por la carretera con remolques/auto cisternas. Desarrollado para utilizarlo en un 75% por carretera, RIDEMAX FL 693 M ofrece excelentes prestaciones por carretera, dando la prioridad al confort y a las propiedades de auto-limpieza. El índice de velocidad clase D/E de la gama es sinónimo de velocidades más elevadas por carretera, con un significativo ahorro de tiempo. La baja resistencia al rodamiento contribuye a un consumo menor de carburante, mientras que la banda de rodadura reforzada y los cinturones de acero aseguran mayor durabilidad.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Camión cisterna • Remolque

Version	STANDARD
Type	TL
Tyre Size	500/60 R 22.5
LI/SS	155 D/152 E

## Dimensions International Standard

Section Width (mm)	503
Overall Diameter (mm)	1172
Static Loaded Radius (mm)	531
Rolling Circumference (mm)	3577
SRI (mm)	550
Rim Rec	AG 16.00
Rim Alt	15.00 ; 17.00
ECE	E4-106R-001402

## Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1320	1495	1775	2095	2400	2665	2985	3270	3550
65	1435	1630	1940	2290	2620	2910	3255	3565	3875
50	1740	1970	2345	2770	3170	3520	3940	4315	4690
40	1955	2215	2635	3110	3560	3955	4430	4850	5270
25	2270	2575	3065	3615	4135	4595	5145	5635	6125
10	2585	2930	3490	4120	4710	5235	5860	6420	6975

Printed on 20/05/2024 21:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..