

RIDEMAX FL 693 M - Especificaciones técnicas



Description

RIDEMAX FL 693 M es el neumático ideal para quien tiene que desplazarse frecuentemente por la carretera con remolques/auto cisternas. Desarrollado para utilizarlo en un 75% por carretera, RIDEMAX FL 693 M ofrece excelentes prestaciones por carretera, dando la prioridad al confort y a las propiedades de auto-limpieza. El índice de velocidad clase D/E de la gama es sinónimo de velocidades más elevadas por carretera, con un significativo ahorro de tiempo. La baja resistencia al rodamiento contribuye a un consumo menor de carburante, mientras que la banda de rodadura reforzada y los cinturones de acero aseguran mayor durabilidad.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Camión cisterna • Remolque

Version	STANDARD
Type	TL
Tyre Size	560/60 R 22.5
LI/SS	161 D/158 E

Dimensions International Standard

Section Width (mm)	543
Overall Diameter (mm)	1244
Static Loaded Radius (mm)	549
Rolling Circumference (mm)	3767
SRI (mm)	600
Rim Rec	AG 16.00
Rim Alt	16.00 ; 17.00 ; AG 20.00
ECE	E4-106R-000630

Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1555	1745	2170	2465	2850	3230	3530	3870	4250
65	1690	1900	2360	2685	3100	3515	3840	4210	4625
50	2050	2300	2860	3250	3755	4260	4650	5100	5600
40	2300	2580	3210	3650	4215	4785	5225	5725	6290
25	2670	3000	3730	4240	4900	5560	6070	6655	7310
10	3040	3415	4250	4830	5580	6330	6910	7580	8325

Printed on 21/05/2024 1:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..