

## RT 747 AGRO INDUSTRIAL - Ficha técnica



### Description

RT 747 AGRO INDUSTRIAL es un neumático radial agro-industrial idóneo para palas compactas y telescópicas. Los tacos extra anchos aseguran un agarre excelente y una extraordinaria estabilidad en las operaciones de levantamiento. El neumático ha sido proyectado con una mezcla particularmente resistente a los cortes y los desgarros. RT 747 AGRO INDUSTRIAL es la mejor respuesta para todas las operaciones agrícolas que en general requieren una versatilidad excepcional.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Cargadora compacta • Elevador telescópico  
Industrial: Cargadora compacta • Elevador telescópico

SIZE	Version	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	TKPH	ECE
<b>11L R 16</b>	STANDARD		122 A8/B	W 8	W 10 L	290	850	0	0		TL		E11-106R-005769
<b>460/70 R 24</b> (17.5L R 24)	STANDARD	R4	152 A8/B	DW 15 L	DW 14 L ; DW 16 L	465	1254	556	3840	575	TL	1	E11-106R-004071
<b>460/70 R 24</b> (17.5L R 24)	STANDARD		159A8/156B	DW 15 L	DW 14 L ; DW 16 L	465	1254	556	3840	575	TL		E11-106R-005105
<b>500/70 R 24</b> (19.5L R 24)	STANDARD	R4	157 A8/154 B	DW 16 L	DW 15 L ; DW 18 L	485	1320	585	3949	625	TL		E11-106R-002988

Printed on 21/05/2024 2:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..