

AGRIMAX FORCE - Spécifications techniques



Description

AGRIMAX FORCE, le produit phare de BKT, est un pneu radial spécialement conçu pour les applications de traitement du terrain, de transport et de récolte avec des tracteurs de grande puissance, auxquels il assure un maximum de performances et d'efficacité. Conçu avec la technologie IF, ce pneu supporte des charges lourdes avec de pressions de gonflage plus basses par rapport à un pneu standard. AGRIMAX FORCE se distingue de par une tringle renforcée en assurant une traction excellente, des excellentes qualités d'autonettoyage, une consommation réduite de carburant ainsi qu'une expérience confortable de conduite.;

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Moissonneuse • Tracteur de forte puissance

Version	SPECIAL
Type	TL
Tyre Size	IF 600/70 R 30 CFO
LI/SS	165 D

Dimensions International Standard

Section Width (mm)	603
Overall Diameter (mm)	1602
Static Loaded Radius (mm)	708
Rolling Circumference (mm)	4800
SRI (mm)	750
Rim Rec	DW 21 B ; DW 21 A
Rim Alt	DW 20 A ; DW 20 B
ECE	E11-106R-006495
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2200	2525	2900	3280	3650	4025	4400	4685
from 65 to 40	2420	2780	3190	3605	4015	4425	4840	5150
30	2515	2890	3315	3745	4175	4600	5030	5355
20	2610	3000	3445	3890	4335	4775	5225	5560
10	3070	3530	4050	4575	5095	5615	6145	6540
Upto 30 Cyc	3145	3610	4145	4685	5215	5750	6290	6695
Upto 15 Cyc	3750	4305	4940	5585	6220	6855	7500	7980
Upto 10 Cyc	4110	4725	5420	6125	6825	7520	8225	8755
10 HT	2515	2890	3315	3745	4175	4600	5030	5355

Printed on 21/05/2024 02:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..