

AGRIMAX RT 600 - Fiche de données

Description

AGRIMAX RT 600 est le pneu idéal pour les pelouses et les applications récolte et pulvérisation. Grâce à sa large zone de contact, AGRIMAX RT 600 garantit une répartition optimisée de la pression sur le terrain en réduisant les dommages sur les prairies et en protégeant le sol. Grâce à la technologie avec épaulement arrondi, la tringle renforcée et un nombre augmenté de crampons, ce pneu garantit une grande stabilité et une traction excellente.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Moissonneuse • Épandeur • Tracteur



| SIZE | Version | USACode | LI/SS | RIM REC | RIM ALT | SW | OD | SLR | RC | Type | ECE |
|--------------------------------------|--------------|----------|--------------|------------------------|-------------------|------|------|------|-------|------|-----------------|
| 620/75 R 26 (23.1 R 26) | STANDARD | 94050444 | 167 A8/B | DW 20 B | | 24.6 | 62.6 | 28.7 | 191 | TL | E11-106R-002993 |
| 750/65 R 26 | STANDARD | 94064311 | 171 A8/B | DW 24 B | DW 23 B ; DW 25 B | 29.5 | 64.4 | 29 | 196.3 | TL | E11-106R-006182 |
| 750/70 R 26 | STANDARD | 94073146 | 172 A8/B | DW 25 B | DW 24 B | 30.7 | 68.9 | 30.9 | 207.4 | TL | E11-106R-007934 |
| 540/65 R 28 | STANDARD | 94053704 | 142 D/145 A8 | W 16 L | W 18 L | 20.9 | 55.6 | 25.3 | 165.4 | TL | E11-106R-002980 |
| 1050/50 R32 | STANDARD | 94040728 | 184 A8/181 B | 36.0 VA | | 41.7 | 73.3 | 32.5 | 224.4 | TL | E4-106R-000813 |
| 650/75 R 32 | STANDARD | 94055968 | 172 A8/B | DW 21 B | DW 20 B ; DW 23 B | 25.8 | 70.4 | 31.8 | 213.2 | TL | E11-106R-004755 |
| 800/65 R 32 (30.5L R 32) | STANDARD | 94044795 | 176 A8/173 B | DW 27 B | DH 27 B ; DW 25 B | 30.5 | 71.7 | 32.4 | 218.8 | TL | E4-106R-001428 |
| 800/65 R 32 (30.5L R 32) | STANDARD | 94039302 | 181 A8/178 B | DW 27 B | DH 27 B ; DW 25 B | 30.5 | 71.7 | 32.4 | 218.8 | TL | E4-106R-001429 |
| 900/60 R 32 | STANDARD | 94062423 | 181 A8/178 B | DW 27 B | DW 28 B ; DW 30 B | 35.3 | 74.5 | 33.1 | 224.3 | TL | E11-106R-005768 |
| IF 1250/50 R 32 CFO | STEEL BELTED | 94070763 | 201 B | VA44/1.7 (multipiece) | | 49.1 | 81.2 | 35.3 | 241.6 | TL | E11-106R-006958 |
| IF 1250/50 R 32 CFO | STEEL BELTED | 94068876 | 201 B | DH44B/1.3 (multipiece) | | 49.1 | 81.2 | 35.3 | 241.6 | TL | E11-106R-006958 |
| IF 680/85 R 32 CFO | STANDARD | 94065486 | 179 D | DW23 B | DW21 B | 26.9 | 77.2 | 33.3 | 230.7 | TL | E11-106R-006401 |
| 650/65 R 38 | STANDARD | 94053667 | 157 D/160 A8 | DW 20 B | | 25.4 | 71.3 | 32.8 | 214.3 | TL | E11-106R-002990 |
| 710/70 R 38 | STANDARD | 94063420 | 178 D/181 A8 | DW 23 B | DW 25 B | 27.8 | 77.1 | 34.7 | 233.3 | TL | E11-106R-006178 |

Printed on 20/05/2024 10:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..