

## AT 625 - Spécifications techniques



### Description

AT 625 est adapté pour les chargeuses-pelleteuses et chargeuses compactes dans toutes les opérations d'excavation et chargement dans le milieu agricole. La bande de roulement extra profonde garantit une meilleure résistance aux perforations et une durabilité plus élevée. AT 625 offre d'excellentes traction et stabilité ainsi qu'une meilleure résistance aux coupures et déchirures.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industriel: Chargeuse-pelleteuse • Chargeuse compacte

Version	STANDARD
Type	TL
Tyre Size	14.9 - 24
LI/SS	145 A8

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	400
Overall Diameter (mm)	1265
Static Loaded Radius (mm)	575
Rolling Circumference (mm)	3800
Rim Rec	DW 13
Rim Alt	DW 11 ; DW 12 ; DW 13 L
TRA Code	R4

## Load capacity (Kg)

km/h / bar	2.90
40	2900

Printed on 21/05/2024 03:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..