

EARTHMAX SR 35 - Spécifications techniques



Description

Earthmax SR 35 est un pneu radial All Steel (Tout Acier) à profil bas particulièrement conçu pour les tombereaux articulés et les chargeuses sur roue. Il est idéal pour les opérations qui exigent des qualités de traction et flotation. Earthmax SR 35 assure d'excellentes traction et stabilité. Sa carcasse robuste avec ceintures en acier lui confère une très longue durabilité ainsi qu'une résistance exceptionnelle aux déchirures et crevaisons.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Tombereau articulé • Bulldozer • Chargeur

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	650/65 R 25 (25/65 R 25)
LI/SS	193 A2

Dimensions US Standard

Usa code	94058624
Overall Width (inch)	25
Overall Diameter (inch)	59
Static Loaded Radius (inch)	26.3
Rolling Circumference (inch)	176.9
Rim Rec	19.50/2.5
Star Rating	*
TRA Code	L3

Load capacity (lbs)

mph / psi	58	62	65	69
5	22000	23400	24000	25400

Printed on 20/05/2024 23:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..