

## EARTHMAX SR 35 - Spécifications techniques



### Description

Earthmax SR 35 est un pneu radial All Steel (Tout Acier) à profil bas particulièrement conçu pour les tombereaux articulés et les chargeuses sur roue. Il est idéal pour les opérations qui exigent des qualités de traction et flotation. Earthmax SR 35 assure d'excellentes traction et stabilité. Sa carcasse robuste avec ceintures en acier lui confère une très longue durabilité ainsi qu'une résistance exceptionnelle aux déchirures et crevaisons.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Tombereau articulé • Bulldozer • Chargeur

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	875/65 R 29 (35/65 R 29)
LI/SS	203 B/214 A2

## Dimensions US Standard

Usa code	94059812
TMPH	191
Overall Width (inch)	35
Overall Diameter (inch)	73.2
Static Loaded Radius (inch)	32.1
Rolling Circumference (inch)	218.9
Rim Rec	27.00/3.50
Rim Alt	27.00/3.0, 28.00/3.5
Star Rating	**/*
TRA Code	E3/L3

## Load capacity (lbs)

mph / psi	58	62	65	69
30	30900	31400	33300	34200
5	40800	43000	45400	46700

Printed on 20/05/2024 20:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..