

# EARTHMAX SR 41 - Spécifications techniques



## Description

EARTHMAX SR 41 est un pneu radial All Steel (Tout Acier) pour les chargeurs et les bulldozers dans les applications de transport, de chargement et de levage. Grâce à sa structure All Steel (Tout Acier) et à son dessin à blocs, EARTHMAX SR 41 offre une excellente résistance aux crevaisons et une plus longue durabilité. Non seulement ce pneu permet d'effectuer de nombreuses heures de travail sans temps d'arrêt machine, mais il offre de plus un confort formidable. EARTHMAX SR 41 (E-4/L-4) est un pneu radial All Steel (Tout Acier) idéal pour les tombereaux articulés, les chargeurs et les bulldozers.

## UM

International Standard

## Construction

 RADIAL

## Machinery

OTR: Tombereau articulé • Bulldozer • Chargeur •  
Tombereau surbaissé

Version	CUT RESISTANT COMPOUND (UMS)
Type	TL
Tyre Size	35/65 R 33

## Dimensions International Standard

Overall Width (mm)	896
Overall Diameter (mm)	2063
Static Loaded Radius (mm)	926
Rolling Circumference (mm)	6283
Rim Rec	28.00/3.5
Rim Alt	--
Star Rating	****
TRA Code	E4

## Load capacity (Kg)

km/h / bar

\* In case of underground mine application, consult your servicing dealer or BKT representative.

Printed on 21/05/2024 06:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..