

EARTHMAX SR 45 M - Spécifications techniques

Description

EARTHMAX SR 45 M est un pneu radial **All Steel** (Tout Acier) particulièrement conçu pour les tombereaux rigides. EARTHMAX SR 45 M assure une excellente traction et il est idéal pour les opérations sur longues distances.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Tombereau rigide



Version	STANDARD COMPOUND
Type	TL
Tyre Size	24.00 R 35
LI/SS	209 B

Dimensions International Standard

TKPH	390
Overall Width (mm)	664
Overall Diameter (mm)	2180
Static Loaded Radius (mm)	980
Rolling Circumference (mm)	6538
Rim Rec	17.00/3.5
Rim Alt	--
Star Rating	**
TRA Code	E4

Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	14000	14500	15500	16000	16500	17000	17500	18000	18500

Printed on 21/05/2024 02:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..