

FL 630 ULTRA - Spécifications techniques



Description

FL 630 ULTRA est un pneu flottaison qui convient pour les applications aux champs et sur route avec remorques, camions-citernes et épandeurs. Grâce au dessin particulier de la bande de roulement et la tringle renforcée, ce pneu est idéal pour une utilisation sur n'importe quel terrain et sur la route. FL 630 ULTRA est synonyme d'un compactage du sol extraordinairement réduit.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Épandeur • Véhicule citerne • Remorque

| | |
|-----------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 560/60 R 22.5 |
| LI/SS | 161 D/172 A8 |

Dimensions International Standard

| | |
|----------------------------|--------------------------|
| Section Width (mm) | 543 |
| Overall Diameter (mm) | 1244 |
| Static Loaded Radius (mm) | 535 |
| Rolling Circumference (mm) | 3760 |
| SRI (mm) | 600 |
| Rim Rec | AG 16.00 |
| Rim Alt | 16.00 ; 17.00 ; AG 20.00 |
| ECE | E11-106R-003013 |

Load capacity (Kg)

| km/h / bar | 0.8 | 1.0 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 |
|------------|------|------|------|------|------|------|------|------|------|------|
| 70 | 1350 | 1540 | 1730 | 2150 | 2445 | 2825 | 3200 | 3495 | 3835 | 4210 |
| 65 | 1480 | 1690 | 1900 | 2360 | 2685 | 3100 | 3515 | 3840 | 4210 | 4625 |
| 50 | 1795 | 2050 | 2300 | 2860 | 3250 | 3755 | 4260 | 4650 | 5100 | 5600 |
| 40 | 2020 | 2305 | 2585 | 3215 | 3655 | 4225 | 4790 | 5230 | 5735 | 6300 |
| 30 | 2240 | 2555 | 2865 | 3565 | 4055 | 4680 | 5310 | 5800 | 6360 | 6985 |
| 25 | 2340 | 2670 | 3000 | 3730 | 4240 | 4900 | 5560 | 6070 | 6655 | 7310 |
| 10 | 2665 | 3040 | 3415 | 4250 | 4830 | 5580 | 6330 | 6910 | 7580 | 8325 |

Printed on 21/05/2024 08:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..