

MULTIMAX MP 522 - Spécifications techniques



Description

MULTIMAX MP 522 est le pneu polyvalent de BKT conçu pour de nombreux domaines d'application dans le secteur agro-industriel. Il est adapté pour toutes les opérations de levage et chargement sur véhicules tels que les chargeurs télescopiques et chargeuses compactes. Stabilité et traction sont ses atouts, associés à une excellente résistance aux crevaisons. Grâce au mélange particulier, MULTIMAX MP 522 garantit une résistance aux coupures et déchirures exceptionnelle.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Chargeuse compacte • Chargeuse télescopique

Industriel: Chargeuse compacte • Chargeuse télescopique

Version	STANDARD
Type	TL
Tyre Size	340/80 R 20 IND
LI/SS	144 A8/B

Dimensions US Standard

Usa code	94052875
Section Width (inch)	13.5
Overall Diameter (inch)	41.4
Static Loaded Radius (inch)	18.9
Rolling Circumference (inch)	126.5
Rim Rec	11
Rim Alt	W10 ; 11 SDC ; W11 ; 12 ; 12 SDC
ECE	E11-106R-002969

Load capacity (lbs)

mph / psi	23	29	35	41	46	51	58	61	64
30	2970	3530	4010	4570	5130	5500	6170	-	-
25	2970	3530	4010	4570	5130	5500	6170	-	-
20	3170	3770	4300	4890	5490	5890	6610	-	-
15	3300	3910	4460	5080	5700	6110	6860	-	-
5 Cvc.	3620	4450	5240	6020	6860	7460	8430	8900	9260
Static	5540	6820	8020	9240	10520	11430	12930	13630	14200

Printed on 21/05/2024 02:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..