

MULTIMAX MP 527 - Spécifications techniques



Description

MULTIMAX MP 527 est un pneu radial polyvalent pour chargeurs télescopiques et chargeuses compactes dans les applications agro-industrielles. Ce pneu présente un dessin à blocs de la bande de roulement qui garantit une excellente traction même sur les surfaces dures. Le flanc robuste du pneu assure une stabilité exceptionnelle en mode levage. MULTIMAX MP 527 est réalisé avec un mélange particulièrement résistant aux coupures et déchirures, ce qui se traduit par une longue vie du pneu.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Chargeuse compacte • Chargeuse télescopique

Industriel: Chargeuse compacte • Chargeuse télescopique

Version	STANDARD
Type	TL
Tyre Size	360/70 R 18 IND
LI/SS	142 A8/B

Dimensions US Standard

Usa code	94053650
Section Width (inch)	14.2
Overall Diameter (inch)	38.1
Static Loaded Radius (inch)	17.3
Rolling Circumference (inch)	113.7
Rim Rec	11
Rim Alt	W10 ; 11 SDC ; W11 ; 12 ; 12 SDC
ECE	E11-106R-002996

Load capacity (lbs)

mph / psi	23	29	35	41	46	51	58	61	64
30	2810	3340	3800	4330	4850	5200	5840	-	-
25	2810	3340	3800	4330	4850	5200	5840	-	-
20	3010	3570	4080	4640	5200	5580	6260	-	-
15	3120	3700	4220	4810	5390	5790	6490	-	-
5 Cyc.	3430	4210	4960	5700	6490	7050	7980	8420	8760
Static	5250	6460	7590	8740	9950	10820	12230	12910	13440

Printed on 21/05/2024 00:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..