

MULTIMAX MP 527 - Spécifications techniques



Description

MULTIMAX MP 527 est un pneu radial polyvalent pour chargeurs télescopiques et chargeuses compactes dans les applications agro-industrielles. Ce pneu présente un dessin à blocs de la bande de roulement qui garantit une excellente traction même sur les surfaces dures. Le flanc robuste du pneu assure une stabilité exceptionnelle en mode levage. MULTIMAX MP 527 est réalisé avec un mélange particulièrement résistant aux coupures et déchirures, ce qui se traduit par une longue vie du pneu.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Chargeuse compacte • Chargeuse télescopique

Industriel: Chargeuse compacte • Chargeuse télescopique

Version	STANDARD
Type	TL
Tyre Size	400/70 R 20 IND (16.0/70 R 20)
LI/SS	149 A8/B

Dimensions International Standard

Section Width (mm)	404
Overall Diameter (mm)	1068
Static Loaded Radius (mm)	494
Rolling Circumference (mm)	3282
SRI (mm)	525
Rim Rec	13
Rim Alt	12 SDC ; 13 SDC ; 14
ECE	E4-106R-002656

Load capacity (Kg)

km/h / bar	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	1560	1855	2115	2405	2700	2895	3250	-	-
40	1560	1855	2115	2405	2700	2895	3250	-	-
30	1675	1985	2265	2580	2890	3100	3480	-	-
25	1735	2060	2350	2675	3000	3215	3610	-	-
10 Cyc.	1905	2340	2755	3170	3610	3925	4440	4680	4875
Static	2920	3590	4225	4860	5535	6020	6805	7180	7475

Printed on 21/05/2024 01:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..