

## RIDEMAX FL 693 M - Spécifications techniques



### Description

RIDEMAX FL 693 M est le pneu idéal pour les applications de transports fréquents sur route avec des remorques/camions-citernes. Conçu pour l'utilisation 75% sur route, RIDEMAX FL 693 M présente des prestations excellentes sur route et priorise aussi le confort et les propriétés d'auto-nettoyage. L'indice de vitesse classe D/E de la gamme est synonyme de vitesse élevée sur la route avec un gain de temps considérable. La résistance au roulement réduite contribue à l'économie de carburant, tandis que la tringle renforcée et les ceintures en acier assurent une durabilité avancée.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Véhicule citerne • Remorque

Version	STANDARD
Type	TL
Tyre Size	425/55 R17
LI/SS	129 D/140 A8

## Dimensions International Standard

Section Width (mm)	420
Overall Diameter (mm)	894
Static Loaded Radius (mm)	397
Rolling Circumference (mm)	2704
SRI (mm)	425
Rim Rec	13.00
ECE	E11-106R-005104

## Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
65	595	760	945	1075	1240	1410	1540	1685	1850
50	720	920	1145	1300	1505	1705	1860	2040	2240
40	800	1025	1275	1450	1675	1900	2075	2275	2500
30	895	1150	1430	1625	1875	2125	2320	2545	2795
25	940	1200	1495	1700	1960	2225	2430	2665	2925
10	1070	1370	1700	1935	2235	2535	2765	3035	3330

Printed on 21/05/2024 00:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..