

## RIDEMAX FL 693 M - Spécifications techniques



### Description

RIDEMAX FL 693 M est le pneu idéal pour les applications de transports fréquents sur route avec des remorques/camions-citernes. Conçu pour l'utilisation 75% sur route, RIDEMAX FL 693 M présente des prestations excellentes sur route et priorise aussi le confort et les propriétés d'auto-nettoyage. L'indice de vitesse classe D/E de la gamme est synonyme de vitesse élevée sur la route avec un gain de temps considérable. La résistance au roulement réduite contribue à l'économie de carburant, tandis que la tringle renforcée et les ceintures en acier assurent une durabilité avancée.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Véhicule citerne • Remorque

Version	STANDARD
Type	TL
Tyre Size	500/50 R 17
LI/SS	149 D/146 E

## Dimensions US Standard

Usa code	94045181
Section Width (inch)	19.8
Overall Diameter (inch)	36.7
Static Loaded Radius (inch)	16.7
Rolling Circumference (inch)	114.7
Rim Rec	16.00
ECE	E4-106R-001821

## Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58	73
45	2180	2450	2980	3370	3900	4430	4890	5360	5890	6610
40	2370	2660	3230	3660	4230	4810	5300	5810	6380	7160
30	2880	3220	3910	4430	5130	5820	6430	7030	7730	8670
25	3230	3620	4390	4970	5750	6540	7220	7900	8670	9740
15	3740	4190	5100	5780	6680	7590	8380	9170	10090	11320
5	4270	4770	5810	6580	7620	8640	9550	10450	11490	12900

Printed on 21/05/2024 06:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..