

XL GRIP (BHL) - Spécifications techniques



Description

XL GRIP (BHL) a été particulièrement conçu pour les chargeuses pelleuses utilisées dans les opérations pénibles lors des applications d'excavation, nivellement et chargement. Le dessin non directionnel de la bande de roulement assure d'excellentes traction et stabilité. Le mélange spécial de la bande de roulement confère une excellente résistance aux coupures et déchirures et allonge la vie du pneu.

UM

International Standard

Construction

 BIAS

Machinery

Industriel: Chargeuse-pelleteuse

Version	INDUSTRIAL
Type	TT
Tyre Size	14.9 - 24
LI/SS	145 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	380
Overall Diameter (mm)	1240
Static Loaded Radius (mm)	575
Rolling Circumference (mm)	3646
Rim Rec	DW 13
Rim Alt	DW 11 ; DW 12 ; DW 13L

Load capacity (Kg)

km/h / bar	2.90
40	2900

Printed on 21/05/2024 08:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..