

AGRIMAX TERIS - Technical Specifications



Description

Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations. Excellent traction properties and high load capacity are its essential features providing best performance in all harvesting operations. The special sidewall protection and a reinforced shoulder increase resistance - thus extending the product life-cycle - also in harsh conditions and if there are stubbles in the fields.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Cotton Picker • Harvester

Version	STANDARD
Type	TL
Tyre Size	620/75 R 30 CHO
LI/SS	168 A8/B

Dimensions US Standard

Usa code	94039586
Section Width (inch)	24.6
Overall Diameter (inch)	66.6
Static Loaded Radius (inch)	30.7
Rolling Circumference (inch)	203.5
Rim Rec	DW 20 B
ECE	E4-106R-001420

Load capacity (lbs)

mph / psi	12	15	20	23	29	35	41	46
30	5690	6550	8020	8770	9630	10490	11360	12350
25	5690	6550	8020	8770	9630	10490	11360	12350
20	6080	7010	8600	9390	10320	11240	12170	13220
10 Cyc	9380	10800	13250	14470	15890	17320	18750	20370
5 Cyc	10230	11780	14450	15780	17340	18890	20450	22220

Printed on 20/05/2024 23:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..