

## AGRIMAX TERIS - Technical Specifications



### Description

Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations. Excellent traction properties and high load capacity are its essential features providing best performance in all harvesting operations. The special sidewall protection and a reinforced shoulder increase resistance - thus extending the product life-cycle - also in harsh conditions and if there are stubbles in the fields.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Cotton Picker • Harvester

Version	STANDARD
Type	TL
Tyre Size	710/55 R 28 CHO
LI/SS	164 A8/B

## Dimensions International Standard

Section Width (mm)	716
Overall Diameter (mm)	1493
Static Loaded Radius (mm)	663
Rolling Circumference (mm)	4442
SRI (mm)	700
Rim Rec	DW 23 B
ECE	E11-106R-005940

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
50	1950	2250	2550	2900	3200	3550	3950	4250	4650	5000
40	1950	2250	2550	2900	3200	3550	3950	4250	4650	5000
30	2090	2410	2730	3105	3425	3800	4230	4550	4980	5350
15 Cyc	3220	3715	4210	4785	5280	5860	6520	7015	7675	8250
10 Cyc	3510	4050	4590	5220	5760	6390	7110	7650	8370	9000

Printed on 20/05/2024 21:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..