

AGRIMAX TERIS - Technical Specifications



Description

Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations. Excellent traction properties and high load capacity are its essential features providing best performance in all harvesting operations. The special sidewall protection and a reinforced shoulder increase resistance - thus extending the product life-cycle - also in harsh conditions and if there are stubbles in the fields.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Cotton Picker • Harvester

Version	STANDARD
Type	TL
Tyre Size	800/65 R 32 CHO (30.5L R 32)
LI/SS	178 A8/175 B

Dimensions International Standard

Section Width (mm)	818
Overall Diameter (mm)	1853
Static Loaded Radius (mm)	838
Rolling Circumference (mm)	5551
SRI (mm)	875
Rim Rec	DW 27 B
Rim Alt	DW 25 B ; DH 27 B
ECE	E4-106R-001430

Load capacity (Kg)

km/h / bar	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.2
50	3175	3660	4485	4900	5455	5865	6420	6900
40	3450	3975	4875	5325	5925	6375	6975	7500
30	3695	4255	5220	5700	6340	6825	7465	8025
15 Cyc	5695	6560	8045	8790	9780	10520	11510	12375
10 Cyc	6210	7155	8775	9585	10665	11475	12555	13500

Printed on 21/05/2024 04:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..