

AGRIMAX V-FLECTO - Technical Specifications



Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the exclusive VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 600/65 R 34 NRO
LI/SS	169 D

Dimensions US Standard

Usa code	94070275
Section Width (inch)	23.5
Overall Diameter (inch)	64.7
Static Loaded Radius (inch)	28.8
Rolling Circumference (inch)	195
Rim Rec	DW 21 B
Rim Alt	DW 20 B
Narrow Rim option	DW 18 L
ECE	E11-106R-007603
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
45	5360	6170	7100	7910	8840	9660	10820	11630
From 40 to 25	5890	6780	7800	8700	9720	10610	11890	12790
20	6010	6910	7960	8870	9920	10820	12140	13040
12	6120	7050	8110	9050	10110	11030	12370	13290
5	6470	7460	8590	9570	10690	11680	13080	14060
*Upto 5 Cyc with front loader	8240	9490	10920	12180	13610	14860	16650	17900
5 HT	6010	6910	7960	8870	9920	10820	12140	13040

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 20/05/2024 22:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..