

# RIDEMAX IT 697 (M+S) - Technical Specifications



## Description

RIDEMAX IT 697 M+S represents the best response to the needs of modern farming contractors during winter operations. It is perfect for haulage and municipality applications. This winter tire for tractors ensures extraordinary grip for all operations on icy and snowy roads without the need of snow chains being mounted. Thanks to the tread grooves and the strong casing, a tractor can be driven in full stability, also at high speed levels. The tread design has been specially developed for heavy-duty services and ensures a low rolling resistance that provides fuel economy plus great stability.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	540/65 R 30 IND
LI/SS	156 D/161 A8

## Dimensions International Standard

Section Width (mm)	530
Overall Diameter (mm)	1464
Static Loaded Radius (mm)	672
Rolling Circumference (mm)	4445
SRI (mm)	700
Rim Rec	W 16 L
Rim Alt	W 18
ECE	E11-106R-003015

## Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2
65	1880	2320	2720	3160	3560	4000
50	2030	2505	2940	3415	3845	4320
40	2175	2685	3145	3655	4115	4625
30	2255	2785	3265	3790	4270	4800

Printed on 20/05/2024 22:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..