

AT 621 - Specifiche tecniche



Description

AT 621 è idoneo per terne e pale compatte in tutte le operazioni di scavo e carico in ambito agricolo. Il battistrada dell'AT 621 è extra profondo per assicurare eccezionale resistenza a tagli e lacerazioni nonché maggiore durabilità. Inoltre, questo pneumatico BKT assicura ottime proprietà di autopulitura. AT 621 è disponibile in svariate versioni per rispondere alle esigenze più diverse degli utilizzatori.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Pala compatta • Terna
Industriale: Terna • Pala caricatrice

| | |
|-----------|-----------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 18.4 - 26 |
| LI/SS | 156 A8 |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Ply Rating | 12 |
| Section Width (mm) | 480 |
| Overall Diameter (mm) | 1425 |
| Static Loaded Radius (mm) | 649 |
| Rolling Circumference (mm) | 4288 |
| Rim Rec | DW 16 L |
| Rim Alt | DW 15 L |
| ECE | E11-106R-003634 |
| TRA Code | R4 |

Load capacity (Kg)

| km/h / bar | 2.50 |
|------------|------|
| 40 | 4000 |

Printed on 20/05/2024 22:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..