

## EARTHMAX SR 35 - Specifiche tecniche



### Description

Earthmax SR 35 è uno pneumatico radiale All Steel a basso profilo specificamente progettato per dumper articolati e pale gommate. È ideale per operazioni che richiedono eccellente trazione e galleggiamento. Earthmax SR 35 assicura sia trazione che stabilità eccellenti. Grazie alla robusta carcassa con cinture in acciaio, lo pneumatico garantisce straordinaria durabilità oltre a resistenza contro strappi e forature.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Dumper articolato • Dozer • Pala caricatrice

|           |                             |
|-----------|-----------------------------|
| Version   | CUT RESISTANT COMPOUND      |
| Type      | TL                          |
| Tyre Size | 650/65 R 25<br>(25/65 R 25) |
| LI/SS     | 193 A2                      |

## Dimensions US Standard

|                              |           |
|------------------------------|-----------|
| Usa code                     | 94058624  |
| Overall Width (inch)         | 25        |
| Overall Diameter (inch)      | 59        |
| Static Loaded Radius (inch)  | 26.3      |
| Rolling Circumference (inch) | 176.9     |
| Rim Rec                      | 19.50/2.5 |
| Star Rating                  | *         |
| TRA Code                     | L3        |

## Load capacity (lbs)

| mph / psi | 58    | 62    | 65    | 69    |
|-----------|-------|-------|-------|-------|
| 5         | 22000 | 23400 | 24000 | 25400 |

Printed on 21/05/2024 06:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..