

EARTHMAX SR 45 M - Specifiche tecniche

Description

EARTHMAX SR 45 M è uno pneumatico radiale **All Steel** particolarmente progettato per dumper rigidi. EARTHMAX SR 45 M assicura ottima trazione ed è ideale per operazioni su lunghe distanze.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dumper rigido



Version	HEAT RESISTANT COMPOUND
Type	TL
Tyre Size	24.00 R 35
LI/SS	209 B

Dimensions US Standard

Usa code	94045921
TMPH	298
Overall Width (inch)	26.1
Overall Diameter (inch)	85.8
Static Loaded Radius (inch)	38.6
Rolling Circumference (inch)	257.4
Rim Rec	17.00/3.5
Rim Alt	--
Star Rating	**
TRA Code	E4

Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	30900	32000	34200	35300	36400	37500	38600	39700	40800

Printed on 21/05/2024 03:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..