

EARTHMAX SR 468 - Specifiche tecniche



Description

EARTHMAX SR 468 è uno pneumatico radiale All Steel specificamente progettato per camion rigidi da trasporto. Il design unico del battistrada con mescole speciali lo rende perfetto per operazioni di scavo su terreni duri, rocciosi e complessi. I blocchi del battistrada con intagli sulla circonferenza e design a intreccio assicurano un'efficace dissipazione del calore. Inoltre, la robusta spalla quadrata aiuta ad espellere i singoli sassi per proteggere lo pneumatico da danneggiamenti. EARTHMAX SR 468 è il frutto della più avanzata tecnologia BKT, sviluppata per trasportare carichi pesanti, garantire una maggiore durata e offrire resistenza ai tagli e alle perforazioni da roccia.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dumper rigido

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	46/90 R 57
LI/SS	252 B

Dimensions International Standard

TKPH	825
Overall Width (mm)	1140
Overall Diameter (mm)	3575
Static Loaded Radius (mm)	1590
Rolling Circumference (mm)	10800
Rim Rec	29.00/6.0
Rim Alt	32.00/6.0
Star Rating	**
TRA Code	E4

Load capacity (Kg)

km/h / bar	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	53000	54500	56000	58000	60000	61500	63000

Printed on 21/05/2024 00:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..