

EARTHMAX SR 484 - Specifiche tecniche



Description

EARTHMAX SR 484 è uno pneumatico radiale All Steel appositamente progettato per dumper rigidi per il trasporto in applicazioni minerarie di superficie. È dotato di un design unico del battistrada E-3 con una speciale miscela che garantisce un'eccellente protezione in condizioni difficili e rocciose, insieme a una maggiore trazione ed eccellenti proprietà autopulenti. La sua costruzione All Steel con cinghie in acciaio multistrato consente una protezione superiore contro urti, fatica e perforazione di rocce, migliorando i tempi di attività e aumentando la produttività. EARTHMAX SR 484 presenta un design quadrato della spalla, che massimizza il contatto con il suolo per un'eccellente manovrabilità e stabilità. Questo pneumatico BKT è stato appositamente progettato per consentire velocità più elevate e lunghi viaggi.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dumper rigido

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	27.00 R 49
LI/SS	223 B

Dimensions International Standard

TKPH	525
Overall Width (mm)	735
Overall Diameter (mm)	2647
Static Loaded Radius (mm)	1193
Rolling Circumference (mm)	8055
Rim Rec	19.50/4.0
Rim Alt	--
Star Rating	**
TRA Code	E3

Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	20600	21800	22400	23000	23600	25000	25750	26500	27250

Printed on 21/05/2024 01:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..