

## EARTHMAX SR 484 - Specifiche tecniche



### Description

EARTHMAX SR 484 è uno pneumatico radiale All Steel appositamente progettato per dumper rigidi per il trasporto in applicazioni minerarie di superficie. È dotato di un design unico del battistrada E-3 con una speciale miscela che garantisce un'eccellente protezione in condizioni difficili e rocciose, insieme a una maggiore trazione ed eccellenti proprietà autopulenti. La sua costruzione All Steel con cinghie in acciaio multistrato consente una protezione superiore contro urti, fatica e perforazione di rocce, migliorando i tempi di attività e aumentando la produttività. EARTHMAX SR 484 presenta un design quadrato della spalla, che massimizza il contatto con il suolo per un'eccellente manovrabilità e stabilità. Questo pneumatico BKT è stato appositamente progettato per consentire velocità più elevate e lunghi viaggi.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Dumper rigido

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	27.00 R 49
LI/SS	223 B

## Dimensions US Standard

Usa code	94067817
TMPH	360
Overall Width (inch)	28.9
Overall Diameter (inch)	104.2
Static Loaded Radius (inch)	47
Rolling Circumference (inch)	317.1
Rim Rec	19.50/4.0
Rim Alt	--
Star Rating	**
TRA Code	E3

## Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	45400	48100	49400	50700	52000	55100	56800	58400	60000

Printed on 20/05/2024 22:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..