

FL 630 ULTRA - Specifiche tecniche



Description

FL 630 ULTRA è idoneo per rimorchi, autobotti e spargitori. Grazie al tallone rinforzato e al particolare disegno del battistrada, è lo pneumatico ideale per un utilizzo polivalente su ogni tipo di terreno o su strada. FL 630 ULTRA è sinonimo di compattazione del terreno straordinariamente ridotta.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Spargitore • Autobotte • Rimorchio

| | |
|-----------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 560/60 R 22.5 |
| LI/SS | 161 D/172 A8 |

Dimensions US Standard

| | |
|------------------------------|--------------------------|
| Usa code | 94052509 |
| Section Width (inch) | 21.4 |
| Overall Diameter (inch) | 49 |
| Static Loaded Radius (inch) | 21.1 |
| Rolling Circumference (inch) | 148 |
| Rim Rec | AG 16.00 |
| Rim Alt | 16.00 ; 17.00 ; AG 20.00 |
| ECE | E11-106R-003013 |

Load capacity (lbs)

| mph / psi | 12 | 15 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------|------|------|------|------|-------|-------|-------|-------|-------|-------|
| 45 | 2980 | 3390 | 3810 | 4740 | 5390 | 6230 | 7050 | 7700 | 8450 | 9280 |
| 40 | 3260 | 3730 | 4190 | 5200 | 5920 | 6830 | 7750 | 8470 | 9280 | 10200 |
| 30 | 3960 | 4520 | 5070 | 6300 | 7160 | 8280 | 9390 | 10250 | 11240 | 12350 |
| 25 | 4450 | 5080 | 5700 | 7090 | 8060 | 9310 | 10560 | 11530 | 12640 | 13890 |
| 20 | 4940 | 5630 | 6320 | 7860 | 8940 | 10320 | 11710 | 12790 | 14020 | 15400 |
| 15 | 5160 | 5890 | 6610 | 8020 | 9350 | 10800 | 12260 | 13380 | 14670 | 16110 |
| 5 | 5870 | 6700 | 7530 | 9370 | 10650 | 12300 | 13950 | 15230 | 16710 | 18350 |

Printed on 20/05/2024 23:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..