

FL 695 - Specifiche tecniche



Description

FL 695 è stato appositamente progettato per i rimorchi in attività edilizie e di trasporto **agricolo** con un esclusivo profilo del battistrada con un blocco centrale. Grazie alla sua robusta carcassa, FL 695 può trasportare carichi pesanti mantenendo la stabilità in tutte le condizioni e il suo battistrada profondo assicura un'ottima autopulizia durante l'uso su strada e fuori strada. La presenza di strati multipli di corde d'acciaio rinforza questo modello contro le forature.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Rimorchio
Industriale: Rimorchio

Version	STEEL BELTED
Type	TL
Tyre Size	600/60 R 30.5
LI/SS	179 D
LI/SS DRIVE WHEEL	179 D
LI/SS FREE ROLLING	179 D

Dimensions International Standard

Section Width (mm)	611
Overall Diameter (mm)	1495
Static Loaded Radius (mm)	693
Rolling Circumference (mm)	4586
SRI (mm)	725
Rim Rec	AG20.00
ECE	E11-106R-008503

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0	5.5	6.0
65	--	--	--	3490	4030	4575	5040	5505	6045	6435	6820	7285	7750
50	--	--	--	4225	4880	5535	6100	6660	7320	7790	8255	8820	9380
40	--	3480	4325	4745	5485	6220	6855	7485	8225	8750	9280	9910	10540
30	2930	3865	4800	5270	6090	6910	7610	8315	9130	9720	10305	11005	11705
25	3065	4045	5025	5515	6370	7225	7960	8695	9555	10165	10780	11515	12245
20	3200	4225	5245	5760	6655	7550	8315	9085	9980	10620	11260	12025	12790
10	3490	4605	5720	6280	7255	8235	9070	9905	10885	11580	12280	13115	13950

Printed on 21/05/2024 02:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..