

FL 695 - Scheda tecnica



Description

FL 695 è stato appositamente progettato per i rimorchi in attività edilizie e di trasporto **agricolo** con un esclusivo profilo del battistrada con un blocco centrale. Grazie alla sua robusta carcassa, FL 695 può trasportare carichi pesanti mantenendo la stabilità in tutte le condizioni e il suo battistrada profondo assicura un'ottima autopulizia durante l'uso su strada e fuori strada. La presenza di strati multipli di corde d'acciaio rinforza questo modello contro le forature.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Rimorchio

Industriale: Rimorchio

SIZE	Version	LI/SS	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
600/55 R 26.5	STEEL BELTED	173 D			AG20.00		591	1335	620	4090	625	TL	E11-106R-007937
650/55 R 26.5	STEEL BELTED	178 D			AG20.00	AG22.00	630	1390	630	4242	675	TL	E11-106R-007052
600/60 R 30.5	STEEL BELTED	179 D	179 D	179 D	AG20.00		611	1495	693	4586	725	TL	E11-106R-008503
710/50 R 30.5	STEEL BELTED	177 D	177 D	177 D	AG24.00	AG20.00	700	1490	691	4553	700	TL	E11-106R-008661

Printed on 21/05/2024 07:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..