

XL GRIP (BHL) - Specifiche tecniche



Description

XL GRIP (BHL) è stato particolarmente sviluppato per terne che vengono impiegate in operazioni pesanti nelle applicazioni di scavo, spianamento e carico. Il disegno non direzionale del battistrada assicura ottima trazione e stabilità. La speciale mescola del battistrada si traduce in eccellente resistenza a tagli e lacerazioni e prolunga la vita del battistrada.

UM

US Standard

Construction

 BIAS

Machinery

Industriale: Terna

Version	STANDARD
Type	TT
Tyre Size	9.00 - 16
LI/SS	132 A6

Dimensions US Standard

Usa code	94051267
Ply Rating	12
Section Width (inch)	10.2
Overall Diameter (inch)	35.8
Rim Rec	6.50 H
Rim Alt	6.00 G

Load capacity (lbs)

mph / psi	83
20	4410

Printed on 20/05/2024 21:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..