

AGRIMAX FORCE - Especificações técnicas



Description

AGRIMAX FORCE, o produto de ponta da BKT, é um pneu radial devidamente projetado para aplicações de tratamento do terreno, de transporte e de colheita com tratores de elevada potência, garantindo máximas prestações e eficiência. Com a tecnologia IF, este pneu permite-lhe transportar cargas pesadas a pressões de enchimento inferiores em comparação com o pneu estandarte reduzindo a compactação do solo. AGRIMAX FORCE é dotado de talão reforçado e assegura uma tração maior, propriedades de autolimpeza e economia de combustível, bem como uma experiência de condução confortável.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Ceifeira • Trator de alta potencia

Version	STANDARD
Type	TL
Tyre Size	IF 650/60 R 34
LI/SS	165 D

Dimensions US Standard

Usa code	94063628
Section Width (inch)	25.6
Overall Diameter (inch)	64.7
Static Loaded Radius (inch)	29.4
Rolling Circumference (inch)	195
Rim Rec	DW 23 B
Rim Alt	DW 21 B
ECE	E11-106R-006014
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
45	4740	5460	6290	7020	7840	8560	9590	10330
from 40 to 25	5210	6010	6920	7720	8620	9410	10550	11355
20	5410	6240	7200	8020	8960	9790	10970	11810
12	5620	6480	7470	8330	9300	10160	11390	12260
5	6610	7630	8780	9800	10950	11950	13390	14420
*Upto 5 Cyc with front loader	7300	8410	9690	10800	12060	13170	14760	15890
5 HT	5410	6240	7200	8020	8960	9790	10970	11810

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 20/05/2024 22:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..