

## AGRIMAX RT 600 - Dados técnicos

### Description

AGRIMAX RT 600 é o pneu apropriado para prados e aplicações para a colheita e o espalhamento. Graças à sua ampla área de contacto, AGRIMAX RT 600 garante uma distribuição de pressão otimizada no terreno reduzindo os danos nos prados e protegendo o solo. Graças à tecnologia com ombros arredondados e um número elevado de blocos, assegura ótima estabilidade e tração.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Ceifeira • Espalhador • Trator



| SIZE                                | Version      | LI/SS        | RIM REC                | RIM ALT           | SW   | OD   | SLR | RC   | SRI | Type | ECE             |
|-------------------------------------|--------------|--------------|------------------------|-------------------|------|------|-----|------|-----|------|-----------------|
| <b>620/75 R 26<br/>(23.1 R 26)</b>  | STANDARD     | 167 A8/B     | DW 20 B                |                   | 625  | 1590 | 730 | 4851 | 750 | TL   | E11-106R-002993 |
| <b>750/65 R 26</b>                  | STANDARD     | 171 A8/B     | DW 24 B                | DW 23 B ; DW 25 B | 750  | 1636 | 737 | 4987 | 775 | TL   | E11-106R-006182 |
| <b>750/70 R 26</b>                  | STANDARD     | 172 A8/B     | DW 25 B                | DW 24 B           | 780  | 1750 | 785 | 5269 | 825 | TL   | E11-106R-007934 |
| <b>540/65 R 28</b>                  | STANDARD     | 142 D/145 A8 | W 16 L                 | W 18 L            | 530  | 1413 | 642 | 4202 | 675 | TL   | E11-106R-002980 |
| <b>1050/50 R32</b>                  | STANDARD     | 184 A8/181 B | 36.0 VA                |                   | 1059 | 1863 | 826 | 5700 | 875 | TL   | E4-106R-000813  |
| <b>650/75 R 32</b>                  | STANDARD     | 172 A8/B     | DW 21 B                | DW 20 B ; DW 23 B | 655  | 1789 | 807 | 5416 | 850 | TL   | E11-106R-004755 |
| <b>800/65 R 32<br/>(30.5L R 32)</b> | STANDARD     | 176 A8/173 B | DW 27 B                | DH 27 B ; DW 25 B | 775  | 1820 | 823 | 5558 | 875 | TL   | E4-106R-001428  |
| <b>800/65 R 32<br/>(30.5L R 32)</b> | STANDARD     | 181 A8/178 B | DW 27 B                | DH 27 B ; DW 25 B | 775  | 1820 | 823 | 5558 | 875 | TL   | E4-106R-001429  |
| <b>900/60 R 32</b>                  | STANDARD     | 181 A8/178 B | DW 27 B                | DW 28 B ; DW 30 B | 896  | 1893 | 841 | 5697 | 900 | TL   | E11-106R-005768 |
| <b>IF 1250/50 R 32<br/>CFO</b>      | STEEL BELTED | 201 B        | VA44/1.7 (multipiece)  |                   | 1247 | 2063 | 897 | 6136 | 975 | TL   | E11-106R-006958 |
| <b>IF 1250/50 R 32<br/>CFO</b>      | STEEL BELTED | 201 B        | DH44B/1.3 (multipiece) |                   | 1247 | 2063 | 897 | 6136 | 975 | TL   | E11-106R-006958 |
| <b>IF 680/85 R 32 CFO</b>           | STANDARD     | 179 D        | DW23 B                 | DW21 B            | 682  | 1960 | 846 | 5860 | 925 | TL   | E11-106R-006401 |
| <b>650/65 R 38</b>                  | STANDARD     | 157 D/160 A8 | DW 20 B                |                   | 645  | 1811 | 833 | 5443 | 875 | TL   | E11-106R-002990 |
| <b>710/70 R 38</b>                  | STANDARD     | 178 D/181 A8 | DW 23 B                | DW 25 B           | 706  | 1959 | 881 | 5926 | 925 | TL   | E11-106R-006178 |

Printed on 20/05/2024 06:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..