

## EARTHMAX SR 313 - Especificações técnicas



### Description

O EARTHMAX SR 313 é um pneu radial integralmente em aço, desenhado para os camiões basculantes articulados e pás carregadoras a trabalhar em terrenos rochosos duros. Com o composto resistente aos cortes e design de piso especial, protege contra os cortes e danos e oferece propriedades de autolimpeza. O design quadrado maximiza o contacto com o solo, garantindo excelente manobrabilidade. A construção radial integralmente em aço com lonas de cima de várias camadas proporciona durabilidade adicional. O EARTHMAX SR 313 é o pneu ideal para transporte, bem como carga e transporte.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Dumper Articulado • Carregadora

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	15.5 R 25
LI/SS	160 B/169 A2

## Dimensions US Standard

Usa code	94066964
TMPH	92
Overall Width (inch)	15.5
Overall Diameter (inch)	49.8
Static Loaded Radius (inch)	22.3
Rolling Circumference (inch)	150.5
Rim Rec	12.00/1.3
Star Rating	**/*
TRA Code	E3/L3

## Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	8050	8550	8800	9350	9650	9900
5	11000	11400	12000	12300	12800	-

Printed on 21/05/2024 03:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..