

## EARTHMAX SR 35 - Especificações técnicas



### Description

Earthmax SR 35 é um pneu radial All Steel, dotado de baixo perfil, especialmente projetado para dumper articulados e pás carregadoras. É ideal para operações que exigem uma excelente tração e flutuação. Earthmax SR 35 assegura tanto tração como estabilidade excelentes. Graças à carcaça robusta com cintos em aço, garante uma duração extraordinária para além da resistência contra rasgões e furos.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Dumper Articulado • Trator de esteira • Carregadora

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	750/65 R 25 (30/65 R 25)
LI/SS	190 B/202 A2

## Dimensions International Standard

TKPH	223
Overall Width (mm)	740
Overall Diameter (mm)	1601
Static Loaded Radius (mm)	715
Rolling Circumference (mm)	4802
Rim Rec	24.00/3.0
Rim Alt	22.00/3.0 ; 25.00/3.0
Star Rating	**/*
TRA Code	E3/L3

## Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75
50	9500	9750	10300	10600
10	13200	14000	14500	15000

Printed on 21/05/2024 07:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..