

## EARTHMAX SR 41 - Especificações técnicas



### Description

EARTHMAX SR 41 é um pneu radial All Steel perfeito para carregadoras e tratores de esteira nas aplicações de transporte, carga e nivelamento. Graças à sua estrutura All Steel e ao desenho caracterizado por blocos, EARTHMAX SR 41 proporciona uma resistência excelente aos furos e uma durabilidade prolongada. Além das muitas horas de trabalho sem ter de parar a máquina, o pneu assegura um conforto excepcional. EARTHMAX SR 41 (E-4/L-4) é um pneu radial All Steel ideal para dumper articulados, pás carregadoras e escavadoras.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Dumper Articulado • Trator de esteira • Carregadora  
• Dumper de baixo perfil

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	26.5 R 25
LI/SS	193 B/202 A2

## Dimensions International Standard

TKPH	185
Overall Width (mm)	678
Overall Diameter (mm)	1742
Static Loaded Radius (mm)	775
Rolling Circumference (mm)	5150
Rim Rec	22.00/3.0
Star Rating	**/*
TRA Code	E4/L4

## Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25
50	9500	9750	10300	10600	11200	11500
10	12850	13200	14000	14500	15000	--

Printed on 21/05/2024 01:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..