

EARTHMAX SR 484 - Especificações técnicas



Description

O EARTHMAX SR 484 é um pneu radial integralmente em aço, desenhado para os camiões basculantes rígidos para o transporte em minas. Apresenta um design exclusivo do piso E-3, com um composto especial que garante excelente proteção em condições difíceis e rochosas, bem como melhor tração e propriedades fantásticas de autolimpeza. A construção integralmente em aço com lonas de cima em aço de várias camadas permite a melhor proteção com os choques, fadiga e a perfuração das rochas, melhorando o tempo de atividade e aumentando a produtividade. O EARTHMAX SR 484 inclui um design quadrado que maximiza o contacto com o solo, garantindo excelente manobrabilidade e estabilidade. Este pneu da BKT foi concebido especialmente para a utilização a velocidades mais altas e a longas distâncias.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dumper Rígido

| | |
|-----------|-------------------|
| Version | STANDARD COMPOUND |
| Type | TL |
| Tyre Size | 27.00 R 49 |
| LI/SS | 223 B |

Dimensions US Standard

| | |
|------------------------------|-----------|
| Usa code | 94067831 |
| TMPH | 418 |
| Overall Width (inch) | 28.9 |
| Overall Diameter (inch) | 104.2 |
| Static Loaded Radius (inch) | 47 |
| Rolling Circumference (inch) | 317.1 |
| Rim Rec | 19.50/4.0 |
| Rim Alt | -- |
| Star Rating | ** |
| TRA Code | E3 |

Load capacity (lbs)

| mph / psi | 73 | 76 | 80 | 83 | 87 | 91 | 94 | 98 | 102 |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 45400 | 48100 | 49400 | 50700 | 52000 | 55100 | 56800 | 58400 | 60000 |

Printed on 21/05/2024 02:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..