

## FL 630 ULTRA - Especificações técnicas



### Description

FL 630 ULTRA é idóneo para aplicações com reboques, cisternas móveis e espalhadores. Gracias ao talão reforçado e o particular desenho do piso do pneu, o pneu é ideal para um uso polivalente em qualquer tipo de terreno o na estrada. FL 630 ULTRA é sinónimo de uma compactação do solo extraordinariamente reduzida.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Espalhador • Cisterna móvel • Reboque

Version	STANDARD
Type	TL
Tyre Size	650/55 R 26.5
LI/SS	169 D/180 A8

## Dimensions US Standard

Usa code	94044269
Section Width (inch)	25.4
Overall Diameter (inch)	54.7
Static Loaded Radius (inch)	23.6
Rolling Circumference (inch)	165.6
Rim Rec	AG 20.00
ECE	E11-106R-006814

## Load capacity (lbs)

mph / psi	12	15	17	23	29	35	41	46	52	58
40	4100	4740	5380	6530	7550	8700	9850	10610	11770	12790
30	4960	5730	6500	7900	9140	10530	11930	12850	14240	15480
25	5640	6530	7410	8990	10410	11990	13580	14640	16230	17640
15	6470	7480	8490	10310	11930	13750	15560	16780	18590	20200
5	7370	8520	9670	11740	13580	15650	17720	19110	21170	23010

Printed on 21/05/2024 05:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..