

## FL 695 - Especificações técnicas



### Description

O FL 695 foi concebido especificamente para atrelados utilizados para transporte nos setores da construção e agricultura, apresentando um padrão de piso único com bloco central. A lona de carcaça resistente permite ao FL 695 transportar cargas pesadas e manter a estabilidade em todas as condições. O piso fundo garante excelente autolimpeza na e fora da estrada. O padrão é reforçado contra furos através de várias camadas de aço.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Reboque

Industrial: Reboque

|           |               |
|-----------|---------------|
| Version   | STEEL BELTED  |
| Type      | TL            |
| Tyre Size | 600/55 R 26.5 |
| LI/SS     | 173 D         |

## Dimensions US Standard

|                              |                 |
|------------------------------|-----------------|
| Usa code                     | 94072897        |
| Section Width (inch)         | 23.3            |
| Overall Diameter (inch)      | 52.6            |
| Static Loaded Radius (inch)  | 24.4            |
| Rolling Circumference (inch) | 161             |
| Rim Rec                      | AG20.00         |
| ECE                          | E11-106R-007937 |

## Load capacity (lbs)

| mph / psi | 012  | 17   | 23    | 29    | 35    | 41    | 46    | 52    | 58    | 65    | 73    | 80    | 87    |
|-----------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 40        | --   | --   | --    | 6450  | 7450  | 8450  | 9310  | 10170 | 11180 | 11890 | 12610 | 13470 | 14330 |
| 30        | --   | --   | --    | 7800  | 9020  | 10240 | 11280 | 12310 | 13520 | 14400 | 15270 | 16300 | 17340 |
| 25        | --   | 6440 | 7990  | 8770  | 10140 | 11510 | 12680 | 13840 | 15210 | 16180 | 17150 | 18320 | 19490 |
| 20        | 5410 | 7140 | 8870  | 9740  | 11250 | 12780 | 14060 | 15370 | 16890 | 17970 | 19050 | 20350 | 21640 |
| 15        | 5670 | 7470 | 9290  | 10200 | 11780 | 13360 | 14730 | 16080 | 17670 | 18790 | 19930 | 21280 | 22640 |
| 10        | 5920 | 7800 | 9700  | 10650 | 12300 | 13950 | 15380 | 16790 | 18450 | 19630 | 20810 | 22230 | 23640 |
| 5         | 6450 | 8520 | 10580 | 11610 | 13410 | 15220 | 16770 | 18320 | 20130 | 21420 | 22710 | 24250 | 25790 |

Printed on 21/05/2024 00:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..