

MULTIMAX MP 522 - Especificações técnicas



Description

MULTIMAX MP 522 é o pneu polivalente da BKT desenvolvido para ser utilizado em muitos campos no setor agroindustrial. É apropriado para todas as operações de elevação e carga em veículos tais como levantadores telescópicos e pás compactas. Estabilidade e tração são os pontos de força associados à resistência excepcional aos furos. Graças ao composto de borracha especial, MULTIMAX MP 522 fornece uma resistência extraordinária aos cortes e lacerações.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Carregadora compacta • Levantador telescópico

Industrial: Carregadora compacta • Levantador telescópico

Version	STANDARD
Type	TL
Tyre Size	540/70 R 24 IND
LI/SS	168 A8/B

Dimensions US Standard

Usa code	94052264
Section Width (inch)	20.9
Overall Diameter (inch)	53.8
Static Loaded Radius (inch)	24.1
Rolling Circumference (inch)	162.7
Rim Rec	DW 16 L
Rim Alt	DW 18 L
ECE	E11-106R-002967

Load capacity (lbs)

mph / psi	23	29	35	41	46	51	58	61	64
30	5930	7040	8020	9140	10250	10990	12350	-	-
25	5930	7040	8020	9140	10250	10990	12350	-	-
20	6350	7540	8600	9790	10980	11770	13220	-	-
15	6590	7830	8920	10150	11390	12210	13710	-	-
5 Cyc.	7230	8900	10470	12040	13710	14910	16850	17780	18520
Static	11080	13630	16050	18460	21020	22860	25850	27260	28390

Printed on 21/05/2024 01:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..