

RT 747 AGRO INDUSTRIAL - Especificações técnicas



Description

RT 747 AGRO INDUSTRIAL é um pneu radial agroindustrial apropriado para retroescavadoras, pás compactas e telescópicas. Os blocos extra largos asseguram uma tração excelente e uma estabilidade extraordinária nas operações de levantamento. Foi projetado com um composto particularmente resistente aos cortes e lacerações para transportar cargas pesadas. RT 747 AGRO INDUSTRIAL é a resposta certa para todas as operações agrícolas que, geralmente, exigem uma versatilidade excepcional.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Carregadora compacta • Levantador telescópico

Industrial: Carregadora compacta • Levantador telescópico

| | |
|-----------|-----------------------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 500/70 R 24 (19.5L R 24) |
| LI/SS | 157 A8/154 B |

Dimensions International Standard

| | |
|----------------------------|-------------------|
| Section Width (mm) | 485 |
| Overall Diameter (mm) | 1320 |
| Static Loaded Radius (mm) | 585 |
| Rolling Circumference (mm) | 3949 |
| SRI (mm) | 625 |
| Rim Rec | DW 16 L |
| Rim Alt | DW 15 L ; DW 18 L |
| ECE | E11-106R-002988 |
| TRA Code | R4 |

Load capacity (Kg)

| km/h / bar | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.0 |
|------------|------|------|------|------|------|------|
| 50 | 1765 | 2175 | 2550 | 2965 | 3340 | 3750 |
| 40 | 1940 | 2395 | 2805 | 3260 | 3670 | 4125 |
| 30 | 2075 | 2560 | 3000 | 3490 | 3930 | 4415 |
| 25 | 2155 | 2655 | 3115 | 3620 | 4075 | 4580 |
| 10 Cyc | 2910 | 3590 | 4210 | 4890 | 5510 | 6190 |
| Static | 4075 | 5025 | 5890 | 6845 | 7710 | 8665 |

Printed on 21/05/2024 00:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..