

XL GRIP (BHL) - Especificações técnicas



Description

XL GRIP (BHL) foi especialmente desenvolvido para retroescavadoras que são utilizadas em operações pesadas nas aplicações de escavação, terraplanagem e carregamento. O desenho não direcional do piso do pneu assegura uma ótima tração e estabilidade. O especial composto de borracha do piso traduz-se numa resistência excelente a cortes e lacerações e prolonga a vida do piso do pneu.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Retroescavadora

Version	STEEL BELTED
Type	TT
Tyre Size	10.00 - 20

Dimensions International Standard

Ply Rating	18
Overall Width (mm)	285
Overall Diameter (mm)	1075
Static Loaded Radius (mm)	505
Rolling Circumference (mm)	3257
Rim Rec	7.5
Rim Alt	7.0

Load capacity (Kg)

km/h / bar	8.30	7.60
10	4480	-
40	-	3305

Printed on 21/05/2024 08:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..