

AT 621 - Specificații tehnice



Descriere

AT 621 este potrivită pentru buldoexcavatoare și încărcătoare compacte în toate operațiunile de săpat și încărcare din agricultură. Anvelopa AT 621 are o bandă de rulare foarte adâncă, care asigură o rezistență mare la tăiere și așchiere și o durabilitate mai mare. În plus, această anvelopă BKT asigură o durabilitate mare și proprietăți de auto-curățare. AT 621 este disponibilă în mai multe versiuni pentru a satisface cele mai diferite cerințe ale utilizatorilor.

UM

US Standard

Construcție

 BIAS

Mașinării

Agricultură: Încărcător compact • Buldoexcavator
Industrial: Buldoexcavator • Încărcător

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	15.5/60 - 18
LI/SS	139 A2

Dimensiuni US Standard

Usa code	94028542
Rating de sarcină	10
Lățimea secțiunii (inch)	15.5
Overall Diameter (inch)	37
Static Loaded Radius (inch)	16.9
Rolling Circumference (inch)	113
Rim Rec	W 13
ECE	E11-106R-003575
TRA Code	R4

Load capacity (lbs)

mph / psi	38
5	5360

Imprimat pe 5/21/2024 8:43 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..