

## EARTHMAX SR 45 M - Specificații tehnice

### Descriere

EARTHMAX SR 45 M este o anvelopă radială cu structură din oțel special concepută pentru camioanele de transport rigide. EARTHMAX SR 45 M asigură tracțiune optimă și este ideală pentru operare pe distanțe lungi. &nbsp;

### UM

US Standard

### Construcție

 RADIAL

### Mașinării

OTR: Autobasculantă rigidă



Versiune	CUT RESISTANT COMPOUND
Tip	TL
Dimensiunea anvelopei	24.00 R 35
LI/SS	209 B

## Dimensiuni US Standard

Usa code	94029907
TMPH	228
Overall Width (inch)	26.1
Overall Diameter (inch)	85.8
Static Loaded Radius (inch)	38.6
Rolling Circumference (inch)	257.4
Rim Rec	17.00/3.5
Rim Alt	--
Star Rating	**
TRA Code	E4

## Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	30900	32000	34200	35300	36400	37500	38600	39700	40800

Imprimat pe 5/21/2024 5:54 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..