

## EARTHMAX SR 468 - Технические спецификации



### Description

EARTHMAX SR 468 — это радиальные шины с цельным металлокордом, специально разработанные для карьерных самосвалов с жесткой рамой. Благодаря уникальному рисунку протектора эти шины, изготовленные с применением специальной резиновой смеси, идеально подходят для эксплуатации на твердых и скалистых грунтах и в суровых условиях горнодобывающих предприятий. Блоки протектора, формирующие грунтозацепы, с продольными канавками и пересекающимися блоками, способствуют рассеиванию тепла. Кроме того, упрочненная прямоугольная плечевая зона гарантирует выталкивание осколков камней из пятна контакта шины во избежание повреждений. EARTHMAX SR 468 была разработана с использованием новейшей технологии BKT, благодаря которой шина может выдерживать повышенную нагрузку. Она отличается долгим сроком службы и сопротивляемостью порезам и проколам от скальных пород.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Производство: Самосвал с жесткой рамой

Version	HEAT RESISTANT COMPOUND
Type	TL
Tyre Size	50/80 R 57
LI/SS	257 B

## Dimensions US Standard

Usa code	94075157
TMPH	918
Overall Width (inch)	47.4
Overall Diameter (inch)	142.1
Static Loaded Radius (inch)	62.9
Rolling Circumference (inch)	428
Rim Rec	32.00/6.0
Rim Alt	29.00/6.0
Star Rating	**
TRA Code	E4

## Load capacity (lbs)

mph / psi	80	83	87	91	94	98	102
30	135500	139000	143500	147500	152000	156500	161000

Printed on 21.05.2024 6:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..