

# EARTHMAX SR 484 - Технические спецификации



## Description

EARTHMAX SR 484 — это радиальная шина с цельным металлокордом, специально разработанная для жесткорамных самосвалов, которые эксплуатируются на открытых выработках. Она отличается уникальным рисунком проектора класса E-3 со специальной резиновой смесью. Благодаря этому шина надежно защищена при эксплуатации на каменистых и прочих сложных поверхностях, а также обеспечивает улучшенную передачу тягового усилия и обладает прекрасной самоочисткой. Металлокордный каркас и многослойный металлокордный брекер гарантируют ей превосходную стойкость к ударам, усталостному разрушению и проколам от камней, что позволяет сократить время простоев и повысить производительность. Шина EARTHMAX SR 484 наделена плечевыми зонами прямоугольного профиля, которые улучшают контакт с дорожным полотном, а это, в свою очередь, положительно сказывается на маневренности и курсовой устойчивости. Эта шина BKT специально рассчитана для движения на повышенных скоростях и протяженных рейсов.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Производство: Самосвал с жесткой рамой

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	27.00 R 49
LI/SS	223 B

## Dimensions International Standard

TKPH	525
Overall Width (mm)	735
Overall Diameter (mm)	2647
Static Loaded Radius (mm)	1193
Rolling Circumference (mm)	8055
Rim Rec	19.50/4.0
Rim Alt	--
Star Rating	**
TRA Code	E3

## Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	20600	21800	22400	23000	23600	25000	25750	26500	27250

Printed on 21.05.2024 7:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..