

EARTHMAX SR 49 M - Технические спецификации



Description

EARTHMAX SR 49 M — это радиальная шина со специальным ненаправленным рисунком протектора, которая спроектирована для погрузочно-доставочных машин (LHD), погрузчиков и бульдозеров, работающих в самых сложных условиях горных разработок, в основном подземных. EARTHMAX SR 49 M идеально подходит для сложных операций, когда требуются исключительные тяговые характеристики и устойчивость. Глубокий рисунок протектора и специально разработанная резиновая смесь шины L-4 для работы в подземных шахтах обеспечивают более долгий срок службы протектора и выдающуюся устойчивость к порезам и проколам камнями.

UM

International Standard

Construction

 RADIAL

Machinery

Производство: Бульдозер • Погрузочно-доставочная машина • Погрузчик • Низкопрофильный самосвал

| | |
|-----------|------------------------|
| Version | CUT RESISTANT COMPOUND |
| Type | TL |
| Tyre Size | 26.5 R 25 |
| LI/SS | 202 A2 |

Dimensions International Standard

| | |
|----------------------------|-----------|
| Overall Width (mm) | 708 |
| Overall Diameter (mm) | 1782 |
| Static Loaded Radius (mm) | 801 |
| Rolling Circumference (mm) | 5297 |
| Rim Rec | 22.00/3.0 |
| Star Rating | * |
| TRA Code | L4 |

Load capacity (Kg)

| km/h / bar | 4.00 | 4.25 | 4.50 | 4.75 | 5.00 |
|------------|-------|-------|-------|-------|-------|
| 10 | 12850 | 13200 | 14000 | 14500 | 15000 |

Printed on 20.05.2024 22:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..