

## EARTHMAX SR 55 - Загрузить лист технических данных



### Description

EARTHMAX SR 55 — это радиальные шины с цельным металлокордом, которые изготовлены специально для погрузчиков, бульдозеров и низкопрофильных самосвалов, работающих в самых сложных условиях горных разработок и разработок карьеров. Благодаря отличной устойчивости к порезам за счет более глубокого и гладкого рисунка протектора шины EARTHMAX SR 55 помогут обеспечить наивысшую эффективность работы и сократить время простоя. При этом они очень прочные. Операторы также оценят превосходную устойчивость и тягу.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Производство: Бульдозер • Погрузочно-доставочная машина • Погрузчик

| SIZE       | Version                | USACode  | TRA Code | Star R | LI/SS  | RIM REC   | RIM ALT              | OW   | OD   | SLR  | RC    | Type |
|------------|------------------------|----------|----------|--------|--------|-----------|----------------------|------|------|------|-------|------|
| 12.00 R 24 | CUT RESISTANT COMPOUND | 94071463 | L5S      | **     | 175 A2 | 8.50/1.3  | 8.0,9.0              | 12   | 50.2 | 22.5 | 149.1 | TT   |
| 12.00 R 24 | CUT RESISTANT COMPOUND | 94071470 | L5S      | **     | 175 A2 | 8.50/1.3  | 8.0,9.0              | 12   | 50.2 | 22.5 | 149.1 | TL   |
| 17.5 R 25  | CUT RESISTANT COMPOUND | 94041015 | L5S      | **     | 182 A2 | 14.00/1.5 |                      | 17.8 | 55.1 | 24.8 | 165.8 | TL   |
| 17.5 R 25  | CUT RESISTANT COMPOUND | 94069941 | L5S      | ***    | 188 A2 | 14.00/1.5 |                      | 17.8 | 55.1 | 24.8 | 165.8 | TL   |
| 18.00 R 25 | CUT RESISTANT COMPOUND | 94053629 | L5S      | **     | 204 A2 | 13.00/2.5 |                      | 20.2 | 65.6 | 28.9 | 191   | TL   |
| 20.5 R 25  | CUT RESISTANT COMPOUND | 94062348 | L5S      | **     | 193 A2 | 17.00/2.0 |                      | 21.1 | 60.7 | 27.6 | 182.8 | TL   |
| 26.5 R 25  | CUT RESISTANT COMPOUND | 94042128 | L5S      | **     | 209 A2 | 22.00/3.0 |                      | 27.2 | 70.3 | 31.9 | 211.6 | TL   |
| 26.5 R 25  | CUT RESISTANT COMPOUND | 94075263 | L5S      | ***    | 214 A2 | 22.00/3.0 |                      | 27.2 | 70.3 | 31.9 | 211.6 | TL   |
| 29.5 R 25  | CUT RESISTANT COMPOUND | 94044160 | L5S      | **     | 216 A2 | 25.00/3.5 |                      | 30.6 | 75.3 | 33.9 | 226.6 | TL   |
| 29.5 R 29  | CUT RESISTANT COMPOUND | 94040193 | L5S      | **     | 218 A2 | 25.00/3.5 | 24.00/3.5, 26.00/3.5 | 30.5 | 79.1 | 35.9 | 238.1 | TL   |
| 35/65 R 33 | CUT RESISTANT COMPOUND | 94070350 | L5S      | ***    | 229 A2 | 28.00/3.5 | --                   | 35.4 | 81.3 | 36   | 243.1 | TL   |
| 35/65 R 33 | CUT RESISTANT COMPOUND | 94061709 | L5S      | **     | 224 A2 | 28.00/3.5 | --                   | 35.4 | 81.3 | 36   | 243.1 | TL   |

Printed on 20.05.2024 20:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..