

TR 463 - Технические спецификации



Description

TR 463 - это шина, специально разработанная для экскаваторов-погрузчиков и промышленных тягачей. За счет поразительной резиновой смеси и прочного каркаса с нейлоновыми нитями корда она демонстрирует выдающиеся результаты при промышленном, строительном и внедорожном вариантах применения. Шина TR 463 гарантирует ведущим колесам выдающуюся тягу.

UM

International Standard

Construction

 BIAS

Machinery

Производство: экскаватор-погрузчик • Трактор-тягач

| | |
|-----------|------------|
| Version | INDUSTRIAL |
| Type | TL |
| Tyre Size | 16.9 - 28 |
| LI/SS | 152 A8 |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Ply Rating | 12 |
| Section Width (mm) | 450 |
| Overall Diameter (mm) | 1405 |
| Static Loaded Radius (mm) | 636 |
| Rolling Circumference (mm) | 4190 |
| Rim Rec | DW 15 L |
| Rim Alt | DW 14 L |
| ECE | E11-106R-003626 |
| TRA Code | R4 |

Load capacity (Kg)

| km/h / bar | 2.60 |
|------------|------|
| 40 | 3550 |

Printed on 21.05.2024 6:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..